

# Infant Incubator BT-500



Infant Incubator

[Read More](#)

SKU:

Price:

Categories: [Delivery](#)

## Product Description

Model BT-500 Infant Incubator Servo temperature control (Manual, Baby, Pre-warm mode) Swivel head and X-rays tray for other procedure Tilting mattress for Trendelenburg treatment Easy removable side walls for easy access and cleaning APGAR timer for 1, 5, 10 minutes LED Examination light for 3 level brightness Air Temp. Control Normal : 23 - 37°C Override : 37.1 - 39°C Measurement 20 - 45 ±0.5°C Skin Temp. Control Normal : 35 - 37.5°C Override : 37.6 - 39°C Measurement 25 - 45 ±0.3°C Humidity Control 30 - 95% Measurement 15 - 99 ±5% RH System Steam (Boiling at 100°C) Water Tank 1,000ml (Autoclavable) Scale (Optional) Measurement 0 - 10Kg ±10g Trend 216 Hour O<sub>2</sub> (Optional) Control 21 - 65 ±5% Measurement 18 - 100 ±5% Masimo SpO<sub>2</sub> (Optional) Measurement 1 - 100% Accuracy ± 3% (70-100%) Unspecified (0~69%) Pulse Rate Range 25 - 240bpm ±3bpm CCD Camera (Optional) Resolution 2.5M pixel Video Transfer Wi-Fi Hood Hand Port 6 Door Tubing Port 2 x 6 Port Structure Double wall Air Curtain Support Noise < 45dB Bed Tilt < 12° Mattress 72 x 39 x 2 cm X-ray tray 35 x 40 cm Lifting Stand (Optional) Height 65 - 85 cm IV Plate (Optional) Load limit 11 Kg IV Pole (Optional) Hook 2 Hook Basket (Optional) Load limit 10 Kg Shelf (Optional) Load limit 3 Kg Air filter Particle 0.3 Micron Efficiency 99.8% General Display 7" TFC Color LCD Trend 72 Hour Alarm 27 Events (Visual & Sound) Warm up < 30 Minute (Fast Mode) Self Test Power On Multi Language Support Quick Guide In-built Dimensions Standard (HWD) 1,354 x 1,024 x 690 mm With Lifting (H) 1,244 - 1,444 mm Weight Standard 99.3 Kg Maximum 117.5 Kg

---